## APPENDIX I:

## THE LISTING OF CLAIMS:

- 1. (currently amended) Controlled release (CR) granules for soil-application obtained by applying an active-ingredient-comprising polymer coating to a solid carrier in a fluidized bed with a defined heat input adjustable to of from about 12,000 11.864 to 25,000 kJ/kg of coating polymer, wherein the CR granules comprise, as coating polymer, a dispersion selected from amongst the following groups group consisting of: butyl acrylate/styrene copolymers, copolymer dispersion of acrylic and methacrylic esters, polyethylene wax emulsions, polyesters composed of the following units: 50 mol% dimethyl terephthalate + approximately 50 mol% adipic acid + 150 mol% 1,4-butanediol and ethylene/methacrylic acid zinc salt.
- 2. (currently amended) The CR granules of defined in claim 1, wherein the with an active-ingredient-comprising polymer coating of comprises components (a) to (c):
  - (a) 0.1-25% by weight of one or more active ingredients,
  - (b) 1-40% by weight of one or more coating polymers, and
  - (c) 0-60% by weight of one ore more additives,
  - and wherein the total of the % by weight of the compounds in the coatings being components (a) to (c) amounts to 100% by weight.
- 3. (canceled)
- 4. (canceled)
- 5. (canceled)
- 6. (canceled)
- 7. (canceled)
- 8. (currently amended) The CR granules of defined in claim 1, comprising, as solid carrier, water-soluble, water-insoluble or biodegradable granules.
- 9. (currently amended) A process for the preparation of the controlled release (CR) granules of claim 1 which contain micropores and are adapted for soil-application, and which are obtained by applying an active-ingredient-comprising coating to a solid carrier in a

- 8 -

fluidized bed with a defined heat input of from about 11,864 to 25,000 kJ/kg of coating polymer, wherein the CR granules comprise, as coating polymer, a dispersion selected from the group consisting of: butyl acrylate/styrene copolymers, copolymer dispersions of acrylic and methacrylic esters, polyethylene wax emulsions, polyesters composed of the following units: 50 mol% dimethyl terephthalate + approximately 50 mol% adipic acid + 150 mol% 1,4-butanediol and ethylene/methacrylic acid zinc salt,

which process comprises applying, to a the carrier, in a fluidized bed:

first the at least one active ingredient, and

then the coating comprising at least one coating polymer and, optionally additives.

in a fluidized bed, said micropores being generated in the coating by abrasion or by the direction use of water-soluble additives.

- 10. (previously presented) A method for controlling phytopathogenic fungi, undesired vegetation, undesired attack by insects and/or for regulating the growth of plants, which comprises applying the CR granules of claim 1 to the soil which contains or will contain seeds or plans therein.
- 11. (canceled)
- 12. (canceled)
- 13. (previously presented) In a process for the preparation of CR granules for soil-application by applying an active-ingredient-comprising polymer coating to a solid carrier in a fluidized bed, the improvement of controlling the release rate of the granules by operating at a heat input to the polymer coating of from 6000 to 25,000 kJ/kg.
- 14. (currently amended) The process of claim 13 wherein the heat input is from about 8200 to about  $\frac{16,000}{16,322}$  kJ/kg.
- 15. (canceled)
- 16. (currently amended) The process of claim 9, wherein the lower heat input level is about 13,000 12,927 kJ/kg.
- 17. (canceled)
- 18. (currently amended) The process of claim 13, wherein the lower heat input level is about 12,000 11,864 kJ/kg.

- 19. (currently amended) The process of claim 13, wherein the lower heat input level is about 13,000 12,927 kJ/kg.
- 20. (new) The CR granules defined in claim 1, which are obtained by applying the polymer coating to the solid carrier with a heat input of from about 12,927 to 25,000 kJ/kg of coating polymer.
- 21. (new) The process of claim 14, wherein the lower heat input level is about 8282 kJ/kg.

- 10 -